Product data sheet


TENTEC ACCENT RECESSED LUMINAIRE, SPOTLIGHT
TL1103506-33-30_23W
SCHMITZ | WILA



IP 20

Tentec accent LED 3000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: TL1103506-33-30 Operating technology: independent driver required Light Technique Light module 361° rotatable, with integrated rotation stop Tilt range from 0-30° CRI > 80 High chromaticity stability with 3SDCM (initial) Constant colour temperature 3000 K Lifetime 50.000 h (L70) Reflector, high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling ring colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Gear boxes suitable for connection to central battery systems Quick installation due to 3-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 23 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 1880 Llm System Efficiency: 72 Llm/W Half-peak Divergence α: 60° Number Luminaires LZ: 0.07 Connector: screw connector, 2 x 1.5 mm2 Reflector Size: R10 Diameter D: 127 mm Cut-out CO: 120 mm Installation Depth RD: 140 mm Total Weight: 0.6 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record TL1103506-33-30_23W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	26 W	LOR	100%
Lamp flux	1880 lm	Total flux	1880 lm
Luminous efficacy	72 lm/W	Total power	26 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 5.51 in
Diameter: 5.00 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 26 W
Appliance Class: II

Protection

IP: 20