Product data sheet


CIRCULAR DOWNWARD Ø2000 RECESSED
CS5C-00W9AZOUEF
LEDSC4



IP 20

LedsC4 Circular Downward ø2000 Recessed CS5C-00W9AZOUEFV1 Pendant for indoor use. For downlighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 12 Product width or diameter (mm): 2060 Product height (mm): 5000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 98W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 12.1. Photobiological risk: RG1. Real flux (lm): 8107. Real lm/W: 75. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 108. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	108 W	LOR	100%
Lamp flux	8107 lm	Total flux	8107 lm
Luminous efficacy	75 lm/W	Total power	108 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 78.74 in
Width: 78.74 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 108 W
Appliance Class: I

Protection

IP: 20