


# Product data sheet

CURVE BLACK 500LM 2700K RA>80 TRAILING EDGE DIMMING  
7021986143409  
SG ARMATUREN



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a down/uplight or as a down or uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK06. Light distribution Direct/Indirect Light technic LED 7W 2700K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK06 Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Tempered glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



1 x LED			
Nominal lamp power	7 W	LOR	100%
Lamp flux	500 lm	ULOR	52%
Luminous efficacy	71 lm/W	Total flux	500 lm
CCT	2700 K	Total power	7 W
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 12.61 in  
Width: 4.07 in  
Height: 2.36 in

## Adjustability

Fixed

## Design

Color of housing: Black

## Electric

System power: 7 W  
Appliance Class: I

## Protection

IP: 65  
IK: 06