


Product data sheet

TK2C L54 60° LE3
TANEK CORNICE EMERGENCY
DEXTRA




Tanek Cornice - 1500mm, IP65, IK10 Cornice mounted luminaire, constructed from robust 1.2mm CR4 steel, opal polycarbonate diffuser, weather resistant and salt spray tested, tamper resistant diffuser fixings, two 20mm side cable entries. Options: LE3 - Lithium Emergency (367 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* WH - White Body BL - Black Body C83 - CRI 80, 3000K

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	32.6 W	CRI	80
Total flux	4063 lm	LOR	100%
Luminous efficacy	125 lm/W	ULOR	4%
		Total power	32.6 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	367 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.22 in

Width: 7.87 in

Height: 4.72 in

Electric

System power: 35.6 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 10

Resistant to impact of balls

Designation labels: CE