## Product data sheet

EVA III 9.751.3066.00









For medium light requirements, mounting height 4.50 - 6.00 m. - Impact-resistant beaded polycarbonate attachment, UV-stabilized - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on a block - Adapter jack for connection - Available in any RAL- or DB - colour without surcharge - For concrete pole with flange plate made of hot galvanized steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

## Light output 1



1 x High pressure mercury	y vapour lamp		
Nominal lamp power	125 W	LOR	83%
Lamp flux	6800 lm	ULOR	22%
Luminous efficacy	41 lm/W	Total flux	5672 lm
CCT	3400 K	Total power	137 W
CBI	54		



1 x High pressure mercury	vapour lamp		
Nominal lamp power	80 W	LOR	83%
Lamp flux	4000 lm	ULOR	22%
Luminous efficacy	37 lm/W	Total flux	3337 lm
CCT	3400 K	Total power	89 W
CBI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 89-137 W

Protection

IP: 55