


# Product data sheet

ALBERTSLUND WALL WHITE 18W TC-TEL  
5743142550  
LOUIS POULSEN



Albertslund Wall Design : Jens Møller-Jensen Concept : The fixture provides characteristic symmetrical and functional lighting. The horizontal ring reflects the light downwards, but its position also allows some light to slip past and illuminate the fixture itself. The anti-glare ring prevents from horizontal glare, and the diffuser is available either as clear or white opal glass, depending on the desired light source. Finish : Galvanized, grey or white, powder coated. Material : Enclosure: Clear glass or partly frosted glass. Saturn ring: Punched aluminium or galvanized, punched steel. Anti glare ring: Spun aluminium or galvanized, extruded steel. Housing: Die cast aluminium. Wall box: Die cast aluminium. Arm: Extruded aluminium. Mounting : Terminal block: 1x3x2.5mm<sup>2</sup>. Cable entries: 2x rear entries for cable Ø 10-14.5mm and 2x bottom knockouts Ø 15mm. Looping: Approved, max. 3x1,5mm<sup>2</sup>. Ballast positioning: In wall box. Class : Ingress protection IP44. Electric shock protection I w. ground. Weight : Max. 3.5kg.

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	18 W	LOR	60%
Lamp flux	1200 lm	ULOR	11%
Luminous efficacy	40 lm/W	Total flux	715 lm
CCT	3000 K	Total power	18 W
CRI	82		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 10.63 in

Diameter: 8.66 in

## Adjustability

Fixed

## Electric

System power: 18 W

Appliance Class: I

## Protection

IP: 44