


Product data sheet

LUMIN. WITH BRACKET NOVARA SAL 6000 SINGLE 3000K
12.12693.0VXXX
HESS




Cast aluminium luminaire body. Luminaire enclosure made of single-pane safety glass, opens without tools. Inclination of the luminaire adjustable in increments: 0°, 10°, 20°, 30°, 40°. Including bracket made of steel, galvanised.


Light output 1




1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	6402 lm	ULOR	100%
Luminous efficacy	121 lm/W	Total flux	6402 lm
CCT	3000 K	Total power	53 W
CRI	80		



1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	7550 lm	ULOR	100%
Luminous efficacy	142 lm/W	Total flux	7550 lm
CCT	3000 K	Total power	53 W
CRI	80		



1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	6085 lm	ULOR	100%
Luminous efficacy	115 lm/W	Total flux	6085 lm
CCT	3000 K	Total power	53 W
CRI	80		




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

53 W
6628 lm
125 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
6628 lm
53 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

53 W
6987 lm
132 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
6987 lm
53 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
4814 lm
130 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
4814 lm
37 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
4984 lm
135 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
100%
4984 lm
37 W




1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
5676 lm
153 lm/W
3000 K
80


LOR
ULOR
Total flux
Total power

100%
100%
5676 lm
37 W



1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	5255 lm	ULOR	100%
Luminous efficacy	142 lm/W	Total flux	5255 lm
CCT	3000 K	Total power	37 W
CRI	80		



1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4576 lm	ULOR	100%
Luminous efficacy	124 lm/W	Total flux	4576 lm
CCT	3000 K	Total power	37 W
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 42.76 in

Width: 14.17 in

Height: 11.77 in

Adjustability

Tiltable

Electric

System power: 37-53 W

Protection

IP: 65