


Product data sheet

VRT4 4L200 OA LE3H
VERTECO 4 EMERGENCY
DEXTRA




Verteco 4 - IP20 Industrial Luminaire with open area optics. Steel body white powder coated paint finish and green polycarbonate end caps. Side entry panel mount with female power feed plug supplied. Options: LE3 - Lithium Emergency (943 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest LE3H - Lithium Emergency High Output (1955 lumens output) LS3H - Lithium Selftest High Output LA3H - Lithium Autotest High Output R18W - Reacta 18 Wide, Presence & Daylight Detection R18U - Reacta 18 Ultra-Wide, Presence & Daylight Detection R18H - Reacta 18 Narrow, Presence & Daylight Detection R18WRF - Reacta 18 Wireless Wide, Presence & Daylight Detection R18URF - Reacta 18 Wireless Ultra-Wide, Presence & Daylight Detection R18HRF - Reacta 18 Wireless Narrow, Presence & Daylight Detection RC18 - Reacta 18, Presence and Daylight RLS10 - Reacta-Link Wireless Presence 10M RLS15 - Reacta-Link Wireless Presence 15M

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	110.9 W	CRI	80
Total flux	18564 lm	LOR	100%
Luminous efficacy	167 lm/W	ULOR	4%
		Total power	110.9 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	1955 lm	LOR	100%
Luminous efficacy	217 lm/W	ULOR	4%
		Total power	9 W

Mounting mode

Pendant

Shape and measurements

Length: 42.32 in

Width: 11.50 in

Height: 1.57 in

Electric

System power: 119.9 W

Ballast: ECG

Controller: DALI

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 20

Designation labels: CE