


Product data sheet

LUMINAIRE WITH BRACKET YORK 4600 3000K
10.14410.0VXXX
HESS




Rectangular luminaire housing with bracket made of cast aluminium. Luminaire enclosure made of single-pane safety glass. Cable connection space in the bracket accessible without tools.


Light output 1




1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	6085 lm	Total flux	6085 lm
Luminous efficacy	115 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	3043 lm	Total flux	3043 lm
Luminous efficacy	152 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2381 lm	Total flux	2381 lm
Luminous efficacy	119 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2294 lm	Total flux	2294 lm
Luminous efficacy	115 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3528 lm	Total flux	3528 lm
Luminous efficacy	126 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3166 lm	Total flux	3166 lm
Luminous efficacy	113 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3299 lm	Total flux	3299 lm
Luminous efficacy	118 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	6331 lm	Total flux	6331 lm
Luminous efficacy	119 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3050 lm	Total flux	3050 lm
Luminous efficacy	109 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4928 lm	Total flux	4928 lm
Luminous efficacy	133 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4961 lm	Total flux	4961 lm
Luminous efficacy	134 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4576 lm	Total flux	4576 lm
Luminous efficacy	124 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	5303 lm	Total flux	5303 lm
Luminous efficacy	143 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4760 lm	Total flux	4760 lm
Luminous efficacy	129 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4587 lm	Total flux	4587 lm
Luminous efficacy	124 lm/W	Total power	37 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	7056 lm	Total flux	7056 lm
Luminous efficacy	133 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	6597 lm	Total flux	6597 lm
Luminous efficacy	124 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		




1 x LED


Nominal lamp power	53 W	LOR	100%
Lamp flux	7053 lm	Total flux	7053 lm
Luminous efficacy	133 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		

**1 x LED**


Nominal lamp power	28 W	LOR	100%
Lamp flux	3043 lm	Total flux	3043 lm
Luminous efficacy	109 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		

**1 x LED**

Nominal lamp power	53 W	LOR	100%
Lamp flux	6100 lm	Total flux	6100 lm
Luminous efficacy	115 lm/W	Total power	53 W
CCT	3000 K		
CRI	80		

**1 x LED**

Nominal lamp power	20 W	LOR	100%
Lamp flux	2480 lm	Total flux	2480 lm
Luminous efficacy	124 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

**1 x LED**

Nominal lamp power	20 W	LOR	100%
Lamp flux	2653 lm	Total flux	2653 lm
Luminous efficacy	133 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 25.36 in

Width: 10.24 in

Height: 4.61 in

Adjustability

Fixed

Electric

System power: 20-53 W

Protection

IP: 66