


Product data sheet

RUNDO 190-261I-10GGMI/830, W
190-261I-10GGMI/830
HALLA




190-261I-10GGMI/830, W Luminaire surface/wall mounted Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 600 x 600 x 62 mm Type of installation: Surface, Wall mounted Distribution: Direct-indirect Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (emergency)




1 x LED			
Nominal lamp power	1.5 W	LOR	100%
Lamp flux	190 lm	Total flux	190 lm
Luminous efficacy	127 lm/W	Total power	1.5 W
CCT	3000 K		
CRI	80		


Light output 2




1 x LED			
Nominal lamp power	39 W	LOR	100%
Lamp flux	4500 lm	ULOR	16%
Luminous efficacy	104 lm/W	Total flux	4500 lm
CCT	3000 K	Total power	43.3 W
CRI	80		




1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	4000 lm	ULOR	16%
Luminous efficacy	104 lm/W	Total flux	4000 lm
CCT	3000 K	Total power	38.3 W
CRI	80		



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	3500 lm	ULOR	16%
Luminous efficacy	105 lm/W	Total flux	3500 lm
CCT	3000 K	Total power	33.2 W
CRI	80		



1 x LED			
Nominal lamp power	25 W	LOR	100%
Lamp flux	3000 lm	ULOR	16%
Luminous efficacy	106 lm/W	Total flux	3000 lm
CCT	3000 K	Total power	28.2 W
CRI	80		



1 x LED			
Nominal lamp power	22 W	LOR	100%
Lamp flux	2500 lm	ULOR	16%
Luminous efficacy	102 lm/W	Total flux	2500 lm
CCT	3000 K	Total power	24.6 W
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 2.44 in
Diameter: 23.62 in

Adjustability

Fixed

Electric

System power: 26.1-44.8 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20