


Product data sheet

LIPROTEC PLUG & PLAY LED-MODULE LLP RGBW
LLP2017AE9
SCHLÜTER-SYSTEMS




Schlüter-LIPROTEC-LLP are plug-and-play LED modules made of a flexible, fully coated LED tube with homogeneous light distribution and an attachment profile made of anodised aluminium (E6/EV1). The LED modules are available in a colour RGB+W version. The LED modules can be integrated into a tile covering, using the trapezoid perforated anchoring leg. Available length: 50 cm 100 cm 200 cm 250 cm Search terms: LIPROTEC, Schlüter, Schlueter, Schluter, LIPROTEC-EASY, LED profile, Bathroom, RGB, RGBW, Tile, Line of light, IP67, Shower, Floor, Fliese

Light output 1 (integrated)




| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 2516 K |
| Nominal lamp power | 0.44 W | CRI | 92 |
| Total flux | 14 lm | LOR | 100% |
| Luminous efficacy | 32 lm/W | Total power | 0.44 W |

Light output 2 (integrated)




| | | | |
|--------------------|---------|-------------|-------|
| Lamp type | LED | CCT | 0 K |
| Nominal lamp power | 0.3 W | CRI | -44 |
| Total flux | 3 lm | LOR | 100% |
| Luminous efficacy | 10 lm/W | Total power | 0.3 W |

Light output 3 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 7289 K |
| Nominal lamp power | 0.2 W | CRI | -29 |
| Total flux | 10 lm | LOR | 100% |
| Luminous efficacy | 50 lm/W | Total power | 0.2 W |

Light output 4 (integrated)



| | | | |
|--------------------|---------|-------------|-------|
| Lamp type | LED | CCT | 0 K |
| Nominal lamp power | 0.4 W | CRI | -29 |
| Total flux | 5 lm | LOR | 100% |
| Luminous efficacy | 12 lm/W | Total power | 0.4 W |

Mounting mode

Wall recessed, Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 0.79 in
Height: 0.67 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic
Color of housing: White, Silver gray

Electric

System power: 1.34 W
Voltage: 24 V DC

Protection

IP: 67
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...149°F