

Product data sheet

MIDPOINT RECESSED - K6
PK6CSE-930AE-BK
LIGHTNET



LED recessed spotlight with surrounding frame for installation in ceilings with cut-out openings. 350° rotatable and 90° tiltable. LED Engine with XICATO ARTIST for highest light quality and colour rendering, including 5 year warranty for colour consistency (MacAdams 3). Alternatively ECO for highest energy efficiency with optimal price-performance ratio and CRI> 90. Colour temperature 2700K, 3000K or 4000K. Replaceable lens reflector optics with spherical facetted optics. Beam angle: 10° (Spot), 20° (Medium), 35° (Flood) or 50° (Wide Flood). Separate Driver included, optionally switchable or dimmable (DALI). Standard clear cover. Optional additional filters or honeycomb grid. Housing and surrounding frame made of aluminium, white, silver, black or champagne coated. Reflector ring also available in gold or copper colours.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	92
Total flux	1374 lm	LOR	100%
Luminous efficacy	65 lm/W	Total power	21 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.10 in
Diameter: 3.54 in

Adjustability

Fixed

Electric

System power: 21 W

Protection