
Product data sheet


MULTIDIR EVO SMALL DOUBLE RECESSED TRIMLESS
AU14-P8W9F1OU60
LEDSC4



IP 54


LedsC4 Multidir Evo Small Double Recessed Trimless AU14-P8W9F1OU60V1 Downlight for indoor use. Adjustable light source. Structure material: Aluminium. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 2.11 Product length (mm): 200 Product width or diameter (mm): 100 Product height (mm): 88 Ø of the hole for recessing (mm): 200x100 Permitted ceiling thickness: 0-20 Class 2. IP: IP54. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 17.3W. Colour temperature: 3000K. Colour rendering index: 92. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 22.5. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 2208. Real lm/W: 112. Voltage / frequency range: 100-240/50-60Hz. Voltage: 33.7. Equipment included: Yes. Total power: 19.8. Power factor: NULL. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED


Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1004 lm	Total flux	1004 lm
Luminous efficacy	110 lm/W	Total power	9.1 W
CCT	3000 K		
CRI	90		



1 x LED


Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1004 lm	Total flux	1004 lm
Luminous efficacy	110 lm/W	Total power	9.1 W
CCT	3000 K		
CRI	90		

Light output 2



1 x LED

Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1104 lm	Total flux	1104 lm
Luminous efficacy	121 lm/W	Total power	9.1 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	9.1 W	LOR	100%
Lamp flux	1104 lm	Total flux	1104 lm
Luminous efficacy	121 lm/W	Total power	9.1 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.87 in
Width: 3.94 in
Height: 0.12 in

Adjustability

Fixed

Electric

System power: 18.2 W
Appliance Class: II

Protection

IP: 54