
Product data sheet


LINEDO_2,3M_AS_1111
9523AS.833.476.003
RZB



IP 54 IK 03


LINEDO, 104 W, 14900 lm, 830, black, DALI Continuous line luminaire, L 2291 B 58 H 76

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	3725 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	26 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	3725 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	26 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	3725 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	26 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	3725 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	26 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 104 W

Protection

IP: 54
IK: 03