

Product data sheet

DKN KREIS
10336.002
RZB




IP
40

IK
02

Series: DKN-Kreis, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 100 Lamp: LED Colour Temperature: 6300K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 290lm System power: 8W Beam Angle: 127° Unified Glare Ratio: 13,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	6300 K
Nominal lamp power	8 W	CRI	60
Total flux	290 lm	LOR	100%
Luminous efficacy	36 lm/W	ULOR	22%
		Total power	8 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.94 in
Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 40
IK: 02