


Product data sheet

DOT SQUARE EYELID
6053-0-2-989-XX
UNILAMP



DOT family is a range of small recessed wall luminaires with LED light sources. The glare-free cover enables DOT to be installed where comfortable illumination is required. Working with world renowned LED manufacturer we have developed DOT to be highly efficient with low energy consumption. DOT is available in 4 different models with interchangeable front covers in both square and round shapes. They have a very small and shallow housing so they can be installed in the wall or step that have limited recessing depth. DOT is widely used to illuminate stairways, pathways and walls where directional low-level light is preferred. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-2 and VDE regulations. • LM6 die-cast aluminium body. • GFR polymer recess box. • LM6 Die Cast Aluminium housing. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate or Safety glass cover. • Post-cured silicone gasket. • High quality LED module. • Option of integrated driver and remote driver in constant current. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	2.1 W	LOR	31%
Lamp flux	260 lm	Total flux	80 lm
Luminous efficacy	124 lm/W	Total power	2.1 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall recessed

Shape and measurements

Length: 3.23 in
Width: 2.95 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 2.1 W
Appliance Class: III

Protection

IP: 65
IK: 07