# Product data sheet

TRIO WHITE 400LM 2700K RA>80 TRAILING EDGE DIMMING 7021986115246

SG ARMATUREN










Square wall luminaire for extra protection of diffuser. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 7W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



1 x LED
Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

7 W
400 lm
57 lm/W
2700 K
80

LOR		
ULOR		
Total flux		
Total power		

100% 21% 400 lm 7 W

### Mounting mode

Wall mounted

## Shape and measurements

Length: 7.09 in Width: 4.37 in Height: 12.60 in

# Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 7 W Appliance Class: I

### Protection

IP: 65 IK: 10