

# Product data sheet

TRIO WHITE 400LM 2700K RA>80 TRAILING EDGE DIMMING


7021986115246

SG ARMATUREN



Square wall luminaire for extra protection of diffuser. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 7W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



### 1 x LED

Nominal lamp power	7 W	LOR	100%
Lamp flux	400 lm	ULOR	21%
Luminous efficacy	57 lm/W	Total flux	400 lm
CCT	2700 K	Total power	7 W
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 7.09 in

Width: 4.37 in

Height: 12.60 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 7 W

Appliance Class: I

## Protection

IP: 65

IK: 10