


Product data sheet

NOTOR 65 DELTA 50-50 1256 LL 840 WHITE START CLO
13660-20944
FAGERHULT



Installation Single or continuous installation via wire suspension or surface mounted. Installation via wire suspension requires wire brackets which provide flexible c/c, see accessories. Can also be wall mounted with special brackets, see Accessories. **Connection** The luminaire is equipped with an access hole for cabling on the top. A special short end with cable entry is used for a surface mounted mains cable, see Accessories. The luminaire unit is equipped with a through-wiring cable (5x1.5 mm²) and a snap-in connection in each end-cap. In a continuous installation, the luminaire row should always begin with a start luminaire. The illuminated corners can be used as a start luminaire and are equipped with through-wiring and quick connection in one end. If creating a closed system one of the corner needs to be used as a start. **Design** Luminaire body enameled in white RAL 9016 G40 alternatively black RAL 9005 G30 or natural anodised extruded aluminium finish. The indirect light is covered by an opal film which generates a wide beam and acts as a dust cover. End caps are included in the Start- and Single-luminaire. Louvre Delta – microprism louvre in acrylic PMMA. **Dimming** CLO Constant Light Output and DALI/Phase-pulse control as standard. **General info** The articles are examples. Use Fagerhult Configure to customise and optimise your version of Notor 65.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	3050 lm	LOR	92%
Luminous efficacy	133 lm/W	Total power	23 W

Mounting mode

Pendant

Shape and measurements

Length: 49.45 in
Width: 2.56 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 23 W

Protection

IP: 20