



Product data sheet

NEPTUN LED COMPACT V2 6000 PC-FROZEN EDD IP66 21 840 / 1200X72X58MM
19.4351.1323.21
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate.
Colour - RAL 9006 (grey). Dimensions: 1200 x 72 x 58 mm. Diffuser: PC-FROZEN (frozen polycarbonate). The efficiency of the optical system is 92,97%. Beam angle: (C0-C180) / (C90-C270) - 119,4° / 104°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 5842,7 lm. Power of luminaire: 38,1 W. Luminaire's light efficiency: 153,4 lm/W.
Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16).
Operating temperature range: -20 ÷ 40° C. Protection degree: IP66. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	38.1 W	LOR	52%
Lamp flux	6285 lm	ULOR	26%
Luminous efficacy	165 lm/W	Total flux	3295 lm
CCT	4000 K	Total power	38.1 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.24 in

Width: 2.83 in

Height: 2.28 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 38.1 W

Controller: DALI

Appliance Class: I

Protection

IP: 66

IK: 10

Other operating numbers

Ambient temperature range: -4...104°F