# Product data sheet

TURE-C 58-283L-10GDM3/840, W
58-283L-10GDM3/840
HALLA

IP 20 IK 02

58-283L-10GDM3/840, W Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 145 x 145 x 240 mm Type of installation: Surface Distribution: Direct Optics type: Plain aluminium reflector Protection class: I Voltage: 220-240V

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 9.6 W | CRI | 80 |
| Total flux | 1310 lm | LOR | 90% |
| Luminous efficacy | 136 lm/W | Total power | 9.6 W |

## Light output 2 (integrated, emergency)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.5 W | CRI | 80 |
| Total flux | 260 lm | LOR | 90% |
| Luminous efficacy | 173 lm/W | Total power | 1.5 W |

### Mounting mode

Ceiling mounted, Pendant

### Shape and measurements

Height: 9.45 in

Diameter: 5.71 in

### Adjustability

Fixed

### Electric

System power: 11.1 W

Appliance Class: I

### Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

### Protection

IP: 20

IK: 02