Product data sheet


LOW GLARE 2 - CCT DIP SWITCH 3000K CRI 90 12W CLD ALUMINIUM
22066777-00
DISANO



IP 40 IK 04

Housing: in die-cast aluminium with springs for recess mounting. Optics: PMMA Coating: epoxy polyester powder coating resistant to UV rays. Heat Sink: built-in. Wiring: DIP switch setting: the fixture comes with a dip switch driver for the setting of the output current. In this way you, can ensure the best luminous flux for any lighting design. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: galvanised steel wire springs for false ceiling mounting.

Light output 1



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1037 lm	Total flux	1037 lm
Luminous efficacy	86 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.28 in
Diameter: 3.54 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 12 W
Appliance Class: II

Protection

IP: 40
IK: 04
Designation labels: CE