



Product data sheet

RUBIN CLEAN LED P SMOOTH 5400 PLX E IP65 34 830 / 620X620MM
19.4046.2511.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 620 x 620 x 78 mm. Weight 5,6 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,22%. Beam angle: (C0-C180) / (C90-C270) - 109,6° / 109,6°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 4318 lm. Power of luminaire: 33,2 W. Luminaire's light efficiency: 130,1 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 12 (B10), 19 (B16), 20 (C10), 32 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK04. Protection against electric shock: I.

Light output 1



2 x LED			
Nominal lamp power	16.6 W	LOR	83%
Lamp flux	2870 lm	Total flux	4791 lm
Luminous efficacy	173 lm/W	Total power	33.2 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in
Width: 24.41 in
Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 33.2 W
Appliance Class: I

Protection

IP: 65
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F