
Product data sheet

EMINERE 4 RGBCW WIDE WALLWASHER


144 ANOLIS





Eminere was designed by Anolis for a wide range of exterior and interior applications with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. Equipped with Anolis' unique 18–bit colour mixing resolution ensures extra fine colour tuning as well as smooth dimming at low level of intensity. Designed in our state of the art R&D facility by industry experts with over 10 years experience in their field, Eminere is IP67 rated and can withstand extreme conditions. Eminere is available in 1, 2, 3, and 4 foot sizes (300/600/900/1200 mm) with RGBW, RGBA or PureWhite single chips as standard and is easy to control, 1 pixel per foot. Eminere fixtures can be used for both permanent and temporary installations, including various architectural and architainment applications.

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	85 W	CRI	79
Total flux	3416 lm	LOR	100%
Luminous efficacy	40 lm/W	Total power	85 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 48.39 in Width: 2.99 in Height: 4.21 in

Adjustability

Tiltable

Electric

System power: 85 W Color adjustable Appliance Class: I

Protection

IP: 67 IK: 06