


Product data sheet

PRO-STRADA MAXI, 108LEDS OPTIEK 5
41368X4X
PROLUMIA




Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95


Light output 1




1 x LED			
Nominal lamp power	123.1 W	LOR	100%
Lamp flux	16500 lm	Total flux	16500 lm
Luminous efficacy	134 lm/W	Total power	123.1 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	130 W	LOR	100%
Lamp flux	16500 lm	Total flux	16500 lm
Luminous efficacy	127 lm/W	Total power	130 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	145.8 W	LOR	100%
Lamp flux	18500 lm	Total flux	18500 lm
Luminous efficacy	127 lm/W	Total power	145.8 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	137.9 W
Lamp flux	17500 lm
Luminous efficacy	127 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	17500 lm
Total power	137.9 W



1 x LED

Nominal lamp power	145.5 W
Lamp flux	19500 lm
Luminous efficacy	134 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	19500 lm
Total power	145.5 W



1 x LED

Nominal lamp power	153.6 W
Lamp flux	19500 lm
Luminous efficacy	127 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	19500 lm
Total power	153.6 W



1 x LED

Nominal lamp power	138 W
Lamp flux	18500 lm
Luminous efficacy	134 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	18500 lm
Total power	138 W



1 x LED

Nominal lamp power	130.6 W
Lamp flux	17500 lm
Luminous efficacy	134 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	17500 lm
Total power	130.6 W

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 26.54 in

Width: 12.09 in

Height: 4.80 in

Electric

System power: 123.1-153.6 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC