


# Product data sheet

I-P65 PLUS L 3H CGLINE+, ALU  
IP65PLA3HCGL  
EATON EMERGENCY LIGHTING




The i-P65+ was developed specifically for requirements in industrial environments. With a combination of high-efficiency LEDs and special optics, the i-P65+ provides optimum performance for a variety of applications. • Robust design with IK08 • i-P65+ L: with wide-beam symmetrical lens • i-P65+ H: with narrow-beam reflector • High lumen output for high spacing and high ceilings • Minimum maintenance effort and increased safety via use of LEDs with high service life (up to 60,000 h)

## Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	10.7 W	CRI	80
Total flux	510 lm	LOR	100%
Luminous efficacy	48 lm/W	Total power	10.7 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	5000 K
Nominal lamp power	10.7 W	CRI	80
Total flux	510 lm	LOR	100%
Luminous efficacy	48 lm/W	Total power	10.7 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 13.39 in

Width: 6.61 in

Height: 3.19 in

## Adjustability

Fixed

## Electric

System power: 21.4 W

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

## Protection

IP: 65

IK: 08