

Product data sheet

FLAT SLIM ROUND
312641.004.76
RZB




IP
40


IK
03

Series: FLAT SLIM round Decorative round LED pendant luminaire. Base: pressure die-cast aluminium, powder-coated. Standard Gore® Protective Vents diaphragm valve to avoid condensation. Canopy made of aluminium, powder-coated. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Glass fastening: bayonet fixing. Uniform lighting achieved by the use of LED panel boards. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. MultiLumen: Multi-step adjustable luminous flux. Factory-set to maximum luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting 3000 K. Dimmable DALI. Colour: silver, matt (approx. RAL 9006) Diameter: 300 mm Height: 75 mm Suspension length: 500-1500 mm Lamp: LED Socket: without socket Colour temperature: 3000K, 4000K Colour rendering index (CRI): 80 System power: 13 W Rated luminous flux: 1250 lm Beam angle Down: 135° Luminous efficiency: 96 lm/W System power 2: 13 W Rated luminous flux 2: 1300 lm Luminous efficiency 2: 100 lm/W System power 3: 26 W Rated luminous flux 3: 2400 lm Luminous efficiency 3: 92 lm/W System power 4: 26 W Rated luminous flux 4: 2500 lm Luminous efficiency 4: 96 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 40


Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	62%
Lamp flux	2500 lm	ULOR	18%
Luminous efficacy	59 lm/W	Total flux	1544 lm
CCT	4000 K	Total power	26 W
CRI	80		




1 x LED			
Nominal lamp power	26 W	LOR	62%
Lamp flux	2400 lm	ULOR	18%
Luminous efficacy	57 lm/W	Total flux	1483 lm
CCT	3000 K	Total power	26 W
CRI	80		



1 x LED

Nominal lamp power	13 W	LOR	62%
Lamp flux	1250 lm	ULOR	18%
Luminous efficacy	59 lm/W	Total flux	772 lm
CCT	3000 K	Total power	13 W
CRI	80		



1 x LED

Nominal lamp power	13 W	LOR	62%
Lamp flux	1300 lm	ULOR	18%
Luminous efficacy	62 lm/W	Total flux	803 lm
CCT	4000 K	Total power	13 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Height: 2.95 in

Diameter: 11.81 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 13-26 W

Protection

IP: 40

IK: 03