

Product data sheet


VOLKMAR III (2-ARMED)
9.870.0206.00
LEIPZIGER LEUCHTEN



IP
55


For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately - Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 42 W | LOR | 55% |
| Lamp flux | 3200 lm | ULOR | 15% |
| Luminous efficacy | 38 lm/W | Total flux | 1748 lm |
| CCT | 2899 K | Total power | 46 W |
| CRI | 90 | | |

Light output 2



| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 42 W | LOR | 55% |
| Lamp flux | 3200 lm | ULOR | 15% |
| Luminous efficacy | 38 lm/W | Total flux | 1748 lm |
| CCT | 2899 K | Total power | 46 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Electric

System power: 92 W

Shape and measurements

Height: 28.35 in

Diameter: 16.14 in

Protection

IP: 55