


Product data sheet

DAMP PROOF DALI 1500 46W 840 IP65 GY
4058075541801
LEDVANCE



Damp-proof luminaires, classic shape, with DALI interface. Product features: High luminous efficacy: up to 139 lm/W. Type of protection: IP65. Beam angle: 110°. Product benefits: High compatibility thanks to DALI-2 certification. Premium driver with up to 100,000 h lifetime. Driver suitable for Emergency escape lighting systems acc. to EN 50172. Driver configuration and dimming possible via mains. Low flicker $\leq 3\%$. 5 years guarantee. Areas of application: Industrial and storage facilities. DALI installations. Car parks and underpasses. Garages. Workshops, assembly lines. Equipment / Accessories: Stainless steel clamps with safety screws included. Mounting accessories included (suspension kit, theft protection kit).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46 W	CRI	80
Total flux	6400 lm	LOR	100%
Luminous efficacy	139 lm/W	ULOR	12%
		Total power	46 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.06 in
Width: 3.23 in
Height: 2.68 in
Weight: 1.74 kg

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Anthracite / graphite

Electric

System power: 46 W
Appliance Class: I

Protection

IP: 65
IK: 08
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...104°F