## Product data sheet


NADJA IV (WALL FITTING BEADED) 9.847.3142.06

LEIPZIGER LEUCHTEN



Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium,burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Hiah	pressure me	ercurv va	oour lamp

5 1			
Nominal lamp power	50 W	LOR	78%
Lamp flux	2000 lm	Total flux	1559 lm
Luminous efficacy	26 lm/W	Total power	59 W
CCT	3400 K		
CRI	54		

1+73-427	tt
	4
	>
	$\times$
XXX	$\sum$
XX+F	X

1 x High pressure mercury v	apour lamp	

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode Wall mounted Shape and measurements

Height: 16.54 in Diameter: 16.54 in

## Electric

System power: 59-89 W

## Protection

IP: 55 Designation labels: CE, F