


# Product data sheet

LOUI 50  
925321.003.1.76  
RZB




IP  
20

IK  
03

Series: LESS IS MORE 50;system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Nur optional: Lichtbandsystem vorbereitet für Seilabhängung! Colour: deep black, matt (RAL;9005) Length: 1681;mm Width: 57;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 40;W Rated luminous flux: 4850;lm Luminous efficiency: 121;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP;20

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 40 W     | CRI         | 80     |
| Total flux         | 4850 lm  | LOR         | 100%   |
| Luminous efficacy  | 121 lm/W | Total power | 40 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 2.24 in  
Width: 66.18 in  
Height: 2.95 in

## Adjustability

Fixed

## Electric

System power: 40 W

## Protection

IP: 20  
IK: 03