Product data sheet

LINEAR LIGHTING

V1-R0-0R828-02OP0-4006040 X-LINE RECTANGLE 0,5 X 1 M 60W 4000K


VARTON



IP 40 IK 01

• Extruded aluminum rectangular luminaire Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,9 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-figury/x-line-pryamougolnik-0-5-kh-1-m/cvetilnik-varton-kh-line-pryamougolnik-60-vt-podvesnoy-4000-k-1050x595x100-mm-ral7045-seryy-muar-s-r/

Light output 1



1 x LED

Nominal lamp power	60 W	LOR	100%
Lamp flux	6600 lm	Total flux	6601 lm
Luminous efficacy	110 lm/W	Total power	60 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 41.34 in

Width: 23.43 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 60 W

Protection

IP: 40

IK: 01