




Product data sheet

RT 44
451169.002
RZB



Series: RT44 Type of Protection: IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz "Base: aluminium, powder-coated; end caps: plastic; diffuser:" plastic, opal. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 900, B 55, H 87 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1350lm System power: 14W Beam Angle: 180°/111° Unified Glare Ratio: 22,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1350 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	19%
		Total power	14 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.17 in
Width: 35.43 in
Height: 3.43 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14 W

Protection

IP: 44
IK: 03