


# Product data sheet

UNILED ISOSAFE DIMTOWARM MATT WHITE 6W LED 2000-2800K RA>95  
5046904211  
SG ARMATUREN



Attractive downlight for indoor and outdoor use. Mounted directly in concrete via the special blade spring system. Well integrated LED chip, dimmable via phase-dimming or DALI driver (not IsoSafe). Made of die-cast powder-coated aluminium with a 10-year corrosion warranty or brushed steel (only indoors), glass diffuser. 42-degree scattering angle via reflector. 35 mm in total height, Flexible hole dimensions Ø76–Ø83. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP54, KL II Light distribution Direct Light technic LED (not exchangeable) 7.3W 2000-2800K Ra>95 SDCM 3 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II SELV IP54 Energy and approvals A++ CE Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 2800 K |
| Nominal lamp power | 7.3 W   | CRI         | 95     |
| Total flux         | 560 lm  | LOR         | 100%   |
| Luminous efficacy  | 77 lm/W | Total power | 7.3 W  |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.70 in  
Width: 3.70 in  
Height: 1.49 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 7.3 W  
Appliance Class: II

## Protection

IP: 54