

# Product data sheet

JUNISTAR ECO ISOSAFE DIMTOWARM WHITE 6W LED 2000-2800K RA>95


5046905215

SG ARMATUREN



Junistar Eco IsoSafe is a cost-efficient downlight for indoor use with a 42° light scattering angle and 30° bidirectional tilt. Made using pressure-moulded, powder-coated aluminium with a white surface and glass shade. Integrated, efficient LED chip offering great quality light. Dimmable with phase control dimmer. We recommend LEDDim 400 and LEDDim Smart. Low installation height and simple assembly straight into the insulation. A flexible diameter of Ø68-83mm makes Junistar Eco a great choice for refurbishing older ceilings. Supplied as an 8-pack. IP44 protection rating Light distribution: Direct Light technic LED (not exchangeable) System wattage: 7W 2000-2800K Ra>95 SDCM 3 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II IP44 Energy and approvals A++ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: Glass Mounting/Connection Recessed, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 105, B16: 168, C10: 105, C16: 168

## Light output 1 (integrated)



Lamp type	LED	CCT	2800 K
Nominal lamp power	7 W	CRI	95
Total flux	510 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	7 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.54 in

Width: 3.54 in

Height: 1.99 in

## Adjustability

Tiltable

## Design

Color of housing: White

## Electric

System power: 7 W

Appliance Class: III

## Protection

IP: 44