


# Product data sheet

VIGILANT LED HIGH BAY 25250 LUMENS, MEDIUM DISTRIBUTION, CLEAR ACRYLIC LENS  
HWE2MC2EDANNGN  
DIALIGHT



Vigilant LED High Bay 25,250 Lumens 186 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Clear Acrylic Lens CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK06 Medium Distribution IP66/67 Scaled IES File

## Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	186 W	CRI	80
Total flux	25250 lm	LOR	100%
Luminous efficacy	136 lm/W	Total power	186 W

## Mounting mode

Pendant

## Shape and measurements

Length: 15.94 in

Width: 15.94 in

Height: 5.04 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 186 W

Appliance Class: I

## Protection

IP: 66

IK: 06

## Other operating numbers

Ambient temperature range: -40...149°F