

Product data sheet

LED FLOOD LIGHT FLD2 200W 3000K

FLD2-200V


MPE



IP
65


- Led flood light - Lamp body made of powder coated aluminum - Lighting surface is protected by tempered glass - Ingress Protection IP65 - Driver is integrated inside the lamp - Size: 414 x 305 x 103 mm - Voltage: 100-240VAC - Power: 200W - Power Factor (PF): >0.9 - Luminance: 20.000 lm - Luminous Efficacy: 100 lm/W - Color Temperature (CCT): 2800-3200K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE – RoHS

Light output 1



1 x LED

Nominal lamp power	200 W	LOR	100%
Lamp flux	24000 lm	ULOR	2%
Luminous efficacy	120 lm/W	Total flux	24000 lm
CCT	3000 K	Total power	200 W
CRI	82		



1 x LED

Nominal lamp power	100 W	LOR	100%
Lamp flux	12000 lm	ULOR	2%
Luminous efficacy	60 lm/W	Total flux	12000 lm
CCT	3000 K	Total power	200 W
CRI	82		

Mounting mode

Pole top mounted

Shape and measurements

Length: 16.30 in

Width: 12.01 in

Height: 4.06 in

Adjustability

Free

Electric

System power: 200 W

Protection

IP: 65