



Product data sheet

GRANVIA PRO 3500 MEDIUM EDD 34 830 / L-900MM
19.4378.4H13.34
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 900 x 72 x 66 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 96,87%. Beam angle: (C0-C180) / (C90-C270) - 61,2° / 61,4°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 3474,4 lm. Power of luminaire: 19 W. Luminaire's light efficiency: 182,9 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: -20 ÷ 35° C. Protection degree: IP20. Impact resistant: IK06. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



3 x LED			
Nominal lamp power	6.333 W	LOR	52%
Lamp flux	1195 lm	Total flux	1880 lm
Luminous efficacy	189 lm/W	Total power	19 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 35.43 in

Width: 2.83 in

Height: 2.60 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W

Controller: DALI

Appliance Class: I

Protection

IP: 20

IK: 06

Other operating numbers

Ambient temperature range: -4...95°F