

Product data sheet

LESS IS MORE 50
312166.000.76
RZB




IP
20

IK
03

Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: extruded anodised aluminium profile. End caps made of plastic, light-deflecting segments made of plastic (ABS) aluminium vapour-plated, highly polished, symmetrical beam, with diffuser made of plastic (PC) opal. Converter included. Lamp (LED) included. Available Colours: anodised aluminium Type of Installation: Ceiling mounting Dimensions: L 1140, B 53, H 65 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3800lm System power: 37W Beam Angle: 60°/58° Number of fittings B10A: 22 Number of fittings B16A: 36 Number of fittings C10A: 37 Number of fittings C16A: 61 Inrush current: 26A Unified Glare Ratio: 16,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	37 W	CRI	80
Total flux	3800 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	37 W

Mounting mode

Ceiling mounted

Electric

System power: 37 W

Shape and measurements

Length: 2.09 in
Width: 44.88 in
Height: 2.56 in

Protection

IP: 20
IK: 03

Adjustability

Fixed