

Product data sheet


PETRA PVI
9.883.8780.61
LEIPZIGER LEUCHTEN



IP
44

Feeder pillar with light designed to supply power to markets, squares and parks and gives personal safety and visual amenity at the same time
Petra P IV: Glazed on one side Petra P VI: Glazed on two sides - Luminaire glazing made of UV-stabilised impact resistant opal polycarbonate. - Luminaire body and head made of hot-dip galvanised steel and available powder coated in any RAL or DB colour as required - One gear tray includes all electrical components - For lamp change luminaire head completely detachable with tool - Luminaire tube with door - Earthing screw on post - Inclusive power unit, IP 44: •1x protection-socket 230 V, 50 Hz/16A •1x CEE-socket 16A 5p 400V •1x LS 16A 3p-C •1x LS 16A 1p-C •1x FI - 40/4/0,03A - Operates with open supply door - Including a three-edge-key M6

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	23 W	LOR	37%
Lamp flux	1500 lm	ULOR	19%
Luminous efficacy	24 lm/W	Total flux	557 lm
CCT	2571 K	Total power	23 W
CRI	90		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 43.31 in
Diameter: 6.69 in

Electric

System power: 23 W

Protection

IP: 44