


Product data sheet

RINGO STAR 60MM SUSPENDED - P3
RP3ASE-830M-D1500-U
LIGHTNET




Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	82
Total flux	2461 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	66%
		Total power	24 W

Mounting mode

Pendant

Shape and measurements

Length: 2.36 in

Width: 22.60 in

Height: 3.94 in

Adjustability

Height adjustable

Electric

System power: 192 W

Protection