


Product data sheet

LUXOR LED SQUARE 6400/840
102255
TREVOS



light fitting for offices, schools etc. for lighting the workspace with high demand on visual performance pursuant to EN 12461-1; optical system with mirrored parabolic louvre without glare, UGR < 19; ON/OFF electronic driver (AC, DC on demand); Body: steel sheet, white (RAL 9003); Diffuser: glossy parabolic louvre, UGR <19; Reflector: steel sheet, white (RAL 9003); Connection: screwless three-pole terminal block; Power: 38,4 W; Luminaire flux: 4170 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK02; Ambient temperature: -25|35 °C; Weight: 6 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.4 W	CRI	80
Total flux	6520 lm	LOR	100%
Luminous efficacy	170 lm/W	ULOR	4%
		Total power	38.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 2.20 in

Adjustability

Fixed

Design

Color of housing: White

Designer: TREVOS

Electric

System power: 38.4 W

Ballast: ECG

Appliance Class: I

Protection

IK: 02

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F