Product data sheet

REKTOR RECESSED LED 3000K FLOOD GE BLACK STRUC 12822132

MODULAR









Guiding the way around your space Rektor is a surprising fixture, as it is highly directional despite the super-sleek housing. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Designed in cooperation with Couvreur-Devos.

Light output 1



1 x LED	
Nominal lamp power	11 V
Lamp flux	1046 In
Luminous efficacy	70 lm/V
CCT	3000 I
CRI	90

minal lamp power	I I W	LOR	/3%
mp flux	1046 lm	Total flux	765 lm
minous efficacy	70 lm/W	Total power	11 W
T	3000 K		
RI	90		



1 x LED			
Nominal lamp power	16.25 W	LOR	73%
Lamp flux	1434 lm	Total flux	1049 lm
Luminous efficacy	65 lm/W	Total power	16.25 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.07 in Width: 3.07 in Height: 4.29 in

Adjustability

Rotatable, Tiltable

Electric

System power: 11-16.25 W

Protection

IP: 20