
Product data sheet


QUADRANA ÖKO
311524.004.2
RZB



IP 40 IK 05

Series: Quadrana Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: toggles. Diffuser: plastic (PMMA), opal. Front: opal, satin finish. With Gore-TM Protective Vents membrane valve as standard. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 300, B 300, H 115 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 190lm System power: 4W Beam Angle: 107° Unified Glare Ratio: 11,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	80
Total flux	190 lm	LOR	100%
Luminous efficacy	48 lm/W	ULOR	20%
		Total power	4 W

Mounting mode

Wall mounted

Shape and measurements

Length: 11.81 in
Width: 11.81 in
Height: 4.53 in

Adjustability

Fixed

Electric

System power: 4 W

Protection

IP: 40
IK: 05