

# Product data sheet


LENA I (SINGLE ARM, CLEAR FROSTED GLAZING)  
9.786.2052.06  
LEIPZIGER LEUCHTEN



IP  
55

Lena I - Post luminaire designed to illuminate squares or streets. Recommended mounting heights between 4.00 m and 5,00 m for medium lighting requirements -Luminaire head made of premium aluminium with a underside finish in a special reflective white paint for maximum light reflection -Excellent street lighting properties provided by computer- optimised reflector system. Reflector made of highest grade aluminium, polished and anodised. Lamps: horizontal mounting -Luminaire glazing made of UV-stabilised impact resistant clear or clear frosted polycarbonate bowl. PMMA Resist available on request -Gear tray made in aluminium, powder coated in white -Simple wiring via a terminal -Including decorative stainless steel bracket -Luminaire head and bracket powder coated in any RAL or DB colour -Please order column with shaft  $\varnothing$  76 mm with 6 threads M8 AZ ... 76/6M8 (full range of columns see page 428 ff) separately

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	85%
Lamp flux	10400 lm	ULOR	5%
Luminous efficacy	77 lm/W	Total flux	8813 lm
CCT	2000 K	Total power	115 W
CRI	25		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 14.17 in

Diameter: 26.38 in

## Adjustability

Height adjustable

## Electric

System power: 115 W

## Protection

IP: 55