# Product data sheet


LED IT STRIP 982520.002.1 RZB



IP 65

Series: LED IT STRIP Flexible fully encapsulated LED strip for indoor and outdoor use. UV/IR resistant TPU potting. LED Pitch 35.7 mm. Solderless connection technology by means of Plug+Play connector system. No need for silicone sealing. Easy separability with commercially available tools (every 250 mm). Smallest bending radius 60 mm. Up to 20 meters LED strip length with only one power supply. One power feed and one end cap included, other accessories can be ordered separately. Colour: white Length: 5000 mm Width: 12 mm Height: 3.4 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 4 W Rated luminous flux: 400 Im Luminous efficiency: 100 Im/W Protection class: III Type of protection: IP&#160:65

# Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

LED 4 W 400 lm 100 lm/W CCT

CRI

LOR

4000 K Total power

80

100%

4 W

### Mounting mode

Ceiling mounted

#### Shape and measurements

Length: 0.47 in Width: 196.85 in Height: 0.12 in

## Adjustability

Fixed

Electric System power: 4 W

Protection

IP: 65