



Product data sheet

RBX L30 E3
 RUBIX LED SUSPENDED EMERGENCY (LINEAR VERSION)
 DEXTRA




Rubix Suspended - 1500mm Suspended Linear Luminaire, white powder coated steel body, 6 x individual cells with opal surround trim for precise optical control. Options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) E3 - Emergency control gear (661 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence P413 - Two point split suspension kit W - White Body B - Black Body GY - GreyBody BK - Black Cell Surround BL - Blue Cell Surround OR - Orange Cell Surround R -Red Cell Surround Continuous Run options: ST - Start of Run section TW - Throughwire section ER - End of run section RBXBD COR TW - Rubix adjustable corner RBXBD BLIND 1260 TW - Rubix Suspended Continuous Run, 1260mm, 6 pole through wire blind unit RBXBD BLIND 1500 TW - Rubix Suspended Continuous Run, 1500mm, 6 pole through wire blind unit RBXBD EC - Rubix End Cap (please specify one set per run of luminaires). RBXBD JOINER - Rubix Joining Kit (required to connect End of Run to Start of Run luminaires where new power feeds are required mid run) P414- 2 point, 3M Suspension Kit

Light output 1 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4.5 W	CRI	80
Total flux	652 lm	LOR	100%
Luminous efficacy	145 lm/W	Total power	4.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.6 W	CRI	80
Total flux	2340 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	19.6 W

Mounting mode

Pendant

Electric

System power: 24.1 W

Ballast: ECG

Shape and measurements

Length: 59.06 in

Width: 9.06 in

Height: 2.01 in

Adjustability

Height adjustable

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Designation labels: CE