
Product data sheet


P.THIRTY SURFACE L-SEG.VER. BLACK U 15MM
P30-ALFV9005C1927L1U
PLANLICHT



IP 20 CE


LED LO 2700K 9,8W 956lm CRI90 https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	1.22 W	CRI	90
Total flux	120 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	1.22 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.22 in
Width: 7.87 in
Height: 22.09 in

Adjustability

Fixed

Electric

System power: 9.8 W

Protection

IP: 20
Designation labels: CE