

Product data sheet

VEKTOR BAS XL 3/4/6,5K


E7220719

CARDI




Vektor Bas är en allmänljusarmatur IP44 med ställbar färgtemperatur 3000K/4000K/6500K och ställbart ljusflöde. Stomme av vitlackerat stål, gavlar av vit biobaserad plast, kupa av återvunnen frostad linjeprismatisk akryl $\geq 20\%$. Monteras dikt tak, lina, på vägg eller konsol. Möjlighet till dos-montage, enligt borranvisning. Armaturen är D-märkt. Kabelinföring $\varnothing 20$ mm i vardera gavel samt 2 st $\varnothing 20$ mm kabelinföring på ovansidan. Insticksplint i mitten av armaturen $5 \times 2 \times 2,5 \text{ mm}^2$.

Light output 1




1 x LED

Nominal lamp power	41 W	LOR	100%
Lamp flux	5750 lm	ULOR	7%
Luminous efficacy	140 lm/W	Total flux	5750 lm
CCT	6500 K	Total power	41 W
CRI	80		




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	3075 lm	ULOR	7%
Luminous efficacy	146 lm/W	Total flux	3075 lm
CCT	6500 K	Total power	21 W
CRI	80		




1 x LED

Nominal lamp power	41 W	LOR	100%
Lamp flux	5885 lm	ULOR	7%
Luminous efficacy	144 lm/W	Total flux	5885 lm
CCT	4000 K	Total power	41 W
CRI	80		




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	3050 lm	ULOR	7%
Luminous efficacy	145 lm/W	Total flux	3050 lm
CCT	4000 K	Total power	21 W
CRI	80		



1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	2875 lm	ULOR	7%
Luminous efficacy	137 lm/W	Total flux	2875 lm
CCT	3000 K	Total power	21 W
CRI	80		



1 x LED

Nominal lamp power	41 W	LOR	100%
Lamp flux	5350 lm	ULOR	7%
Luminous efficacy	130 lm/W	Total flux	5350 lm
CCT	3000 K	Total power	41 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 45.43 in

Width: 6.41 in

Height: 1.43 in

Adjustability

Fixed

Electric

System power: 21-41 W

Appliance Class: I

Protection

IP: 44

IK: 06