


# Product data sheet

ELLK 92036/36 CG-S  
12266881103  
EATON EMERGENCY LIGHTING




Explosion protected luminaire for tubular fluorescent lamps, with CEWA GUARD monitoring and 20 digit address switch

## Light output 1



2 x Fluorescent lamp tubular T5			
Nominal lamp power	36 W	Socket	G13
Lamp flux	3350 lm	LOR	85%
Luminous efficacy	79 lm/W	ULOR	10%
CCT	3000 K	Total flux	5685 lm
CRI	85	Total power	72 W

## Light output 2 (emergency)



1 x Fluorescent lamp tubular T5			
Nominal lamp power	36 W	Socket	G13
Lamp flux	3350 lm	LOR	82%
Luminous efficacy	77 lm/W	ULOR	9%
CCT	4000 K	Total flux	2759 lm
CRI	85	Total power	36 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 53.54 in  
Width: 7.40 in  
Height: 5.12 in

## Adjustability

Fixed

## Electric

System power: 108 W  
Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency power supply: Central battery feed-in  
Emergency sign: N/A

## Protection

IP: 66  
IK: 03